

Patent
Attorney Dkt.: LYNN/0153.A

IN THE CLAIMS:

Please amend the following claims according to the following replacement claim set:

1. (Currently Amended) An apparatus comprising:
a porous anode substrate in fluid communication with a source of hydrogen gas;
a porous cathode substrate in fluid communication with a source of nitrogen gas; and
~~an~~ a liquid electrolyte disposed within a matrix, wherein the matrix is disposed between the
porous anode substrate and the porous cathode substrate, and wherein the liquid electrolyte is not an
aqueous solution.
2. (Original) The apparatus of claim 1, further comprising:
a catalyst disposed on the anode substrate facing the electrolyte matrix.
3. (Original) The apparatus of claim 1, further comprising:
a catalyst disposed on the cathode substrate facing the electrolyte matrix.
4. (Original) The apparatus of claim 1, wherein the porous anode substrate has a porosity greater than 40 percent.
5. (Original) The apparatus of claim 1, wherein the porous anode substrate has a porosity greater than 90 percent.
6. (Original) The apparatus of claim 1, further comprising:
a metal membrane having a thickness of between 1 and 200 microns disposed on the porous anode substrate facing the electrolyte matrix.
7. (Currently Amended) The apparatus of claim 6, wherein the metal membrane is made from a metal selected from palladium, a palladium alloy, iron, tantalum, lanthanide metals, ~~and or~~ combinations thereof.

Patent
Attorney Dkt.: LYNN/0153.A

8. (Currently Amended) The apparatus of claim 6, further comprising a matrix supporting the metal membrane, wherein the matrix is formed from a material selected from nickel and or nickel-containing alloys.
9. (Currently Amended) The apparatus of claim 6, further comprising a matrix supporting the metal membrane, wherein the matrix is formed from a material selected from transition metals and or transition metal-containing alloys.
10. (Original) The apparatus of claim 6, further comprising a matrix supporting the metal membrane, wherein the matrix is formed from an electrically conducting inorganic ceramic material.
11. (Original) The apparatus of claim 1, further comprising:
a metal membrane having a thickness of between 1 and 200 microns disposed on both sides of the porous anode substrate, wherein the porous anode substrate is a non-noble metal and the metal membrane is palladium or a palladium-containing alloy.
12. (Currently Amended) The apparatus of claim 11, wherein the non-noble metal is selected from iron, tantalum, and or lanthanide metals.
13. (Original) The apparatus of claim 6, wherein a catalyst is disposed on a surface of the metal membrane facing the electrolyte.
14. (Currently Amended) The apparatus of claim 13, wherein the catalyst comprises a metal selected from iron, ruthenium and or combinations thereof.
15. (Original) The apparatus of claim 1, wherein the porous cathode substrate is made from nickel, a nickel-containing compound, or a nickel alloy.
16. (Original) The apparatus of claim 1, wherein the porous cathode substrate is made from metal,

Patent
Attorney Dkt.: LYNN/0153.A

metal alloy, ceramic or a combination thereof.

17. (Original) The apparatus of claim 1, wherein the porous cathode substrate has a pore size of about 0.2 microns.

18. (Original) The apparatus of claim 1, wherein the electrolyte supports migration of negatively charged nitrogen-containing species between the cathode substrate and the anode.

19. (Original) The apparatus of claim 1, wherein the electrolyte comprises a molten salt.

20. (Original) The apparatus of claim 19, wherein the molten salt comprises one or more metal chlorides.

21. (Currently Amended) The apparatus of claim 19, wherein the molten salt comprises one or more metal salts selected from chlorides, iodides, bromides, sulfides, phosphates, carbonates, and or mixtures thereof.

22. (Original) The apparatus of claim 19, wherein the molten salt comprises lithium chloride and potassium chloride.

23. (Original) The apparatus of claim 22, wherein the molten salt further comprises a metal nitride salt.

24. (Original) The apparatus of claim 22, wherein the molten salt electrolyte has a greater molar concentration of lithium chloride than potassium chloride.

25. (Original) The apparatus of claim 22, wherein the molten salt electrolyte further comprises rubidium chloride, cesium chloride, ruthenium chloride, iron chloride, or a mixture thereof.

26. (Currently Amended) An apparatus comprising:

Patent
Attorney Dkt.: LYNN/0153.A

a plurality of electrolytic cells and a bipolar plate separating each of the plurality of electrolytic cells, wherein each of the plurality of electrolytic cells comprises:

- a porous anode substrate in fluid communication with a source of hydrogen gas;
- a porous cathode substrate in fluid communication with a source of nitrogen gas;
- an a liquid electrolyte disposed within a matrix placed between the porous anode substrate and the porous cathode substrate, wherein the liquid electrolyte is not an aqueous solution;
- an anodic fluid flowfield in fluid communication with the porous anode substrate opposite the matrix; and
- a cathodic fluid flowfield in fluid communication with the porous cathode substrate opposite the matrix.

27. (Currently Amended) The apparatus of claim 26, wherein the anodic fluid flowfield has a first face that is in electronic communication with the porous anode substrate and a second face in electronic communication with a first bipolar plate, and wherein the cathodic fluid flowfield has a first face that is in electronic communication with the porous cathode substrate and a second face in electronic communication with a second bipolar plate.

28. (Original) The apparatus of claim 26, further comprising:

- a hydrogen gas manifold for providing fluid communication between the source of hydrogen gas and each of the anodic fluid flowfields; and
- a nitrogen gas manifold for providing fluid communication between the source of nitrogen gas and each of the cathodic fluid flowfields.

29. (Currently Amended) The apparatus of claim 28, wherein the hydrogen gas manifold and the nitrogen gas manifold are each selected from an internal manifold and or an external manifold.

30. (Currently Amended) The apparatus of claim 26, wherein the porous anode substrate and the porous cathode substrate are each selected from metal foams, metal grids, sintered metal particles, sintered metal fibers, and or combinations thereof.

Patent
Attorney Dkt.: LYNN/0153.A

31. (Original) The apparatus of claim 26, wherein the anodic fluid flowfield is metallurgically bonded to the bipolar plate.
32. (Currently Amended) The apparatus of claim 31, wherein the metallurgical bonds are formed by a process selected from welding, brazing, soldering, sintering, fusion bonding, vacuum bonding, and or combinations thereof.
33. (Original) The apparatus of claim 26, wherein the cathodic fluid flowfield is metallurgically bonded to the bipolar plate.
34. (Original) The apparatus of claim 26, wherein the anodic fluid flowfield is metallurgically bonded to the porous anode substrate.
35. (Original) The apparatus of claim 26, wherein the cathodic fluid flowfield is metallurgically bonded to the porous cathode substrate.
36. (Currently Amended) The apparatus of claim 26, wherein the porous cathode substrate is selected from metal carbides, metal borides and or metal nitrides.
37. (New) The apparatus of claim 1, wherein the electrolyte comprises a salt dissolved in an organic solvent.
38. (New) The apparatus of claim 1, wherein the electrolyte comprises low temperature molten salts.
39. (New) The apparatus of claim 26, wherein the electrolyte comprises a molten salt.
40. (New) The apparatus of claim 39, wherein the molten salt is charged with a nitride salt.
41. (New) The apparatus of claim 39, wherein the molten salt is charged with a nitride compound,

Patent
Attorney Dkt.: LYNN/0153.A

an azide compound, or a combination thereof.

42. (New) The apparatus of claim 39, wherein the molten salt comprises lithium chloride and potassium chloride.

43. (New) The apparatus of claim 39, wherein the molten salt further comprises rubidium chloride, cesium chloride, ruthenium chloride, iron chloride or a mixture thereof.

44. (New) The apparatus of claim 39, wherein the molten salt comprises one or more metal chlorides.

45. (New) The apparatus of claim 39, wherein the molten salt comprises one or more metal salts selected from chlorides, iodides, bromides, sulfides, phosphates, carbonates or mixtures thereof.

46. (New) The apparatus of claim 26, wherein the electrolyte comprises a low temperature molten salt.

47. (New) The apparatus of claim 26, wherein the electrolyte comprises a salt dissolved in an organic solvent.